


GROOVE 304L Grooved-end pipe

Family: NA60GRGR · 28 variants



Product image



Technical drawing

Product description

TAVINOX GROOVE grooved fitting in AISI 304L (1.4307) stainless steel. The clamping coupling with an EPDM elastomer gasket and the TGS rolled groove allows fast installation without welding, with high resistance to vibration and the option to dismantle the joint. Intended for a nominal pressure up to 1.6 MPa; drinking water up to 80 °C, other media (e.g. heating) up to 110 °C.

Dimension table

Code	DN	OD	EAN	T (mm)	L (m)	D	L	Bag	Box
NA60GRGR.12525.1000	DN125	133	08596683018187	2.5	1	133	1,000	1	1
NA60GRGR.12525.3000	DN125	133	08596683018392	2.5	3	133	3,000	1	1
NA60GRGR.12525.500	DN125	133	08596683017975	2.5	0.5	133	500	1	1
NA60GRGR.12525.6000	DN125	133	08596683018606	2.5	6	133	6,000	1	1
NA60GRGR.1253.1000	DN125	133	08596683018217	3	1	133	1,000	1	1
NA60GRGR.1253.3000	DN125	133	08596683018422	3	3	133	3,000	1	1
NA60GRGR.1253.500	DN125	133	08596683018002	3	0.5	133	500	1	1
NA60GRGR.1253.6000	DN125	133	08596683018637	3	6	133	6,000	1	1
NA60GRGR.15025.1000	DN150	159	08596683018248	2.5	1	159	1,000	1	1
NA60GRGR.15025.3000	DN150	159	08596683018453	2.5	3	159	3,000	1	1
NA60GRGR.15025.500	DN150	159	08596683018033	2.5	0.5	159	500	1	1
NA60GRGR.15025.6000	DN150	159	08596683018668	2.5	6	159	6,000	1	1
NA60GRGR.1503.1000	DN150	159	08596683018279	3	1	159	1,000	1	1
NA60GRGR.1503.3000	DN150	159	08596683018484	3	3	159	3,000	1	1
NA60GRGR.1503.500	DN150	159	08596683018064	3	0.5	159	500	1	1
NA60GRGR.1503.6000	DN150	159	08596683018699	3	6	159	6,000	1	1
NA60GRGR.2003.1000	DN200	219	08596683018309	3	1	219	1,000	1	1
NA60GRGR.2003.3000	DN200	219	08596683018514	3	3	219	3,000	1	1
NA60GRGR.2003.500	DN200	219	08596683018095	3	0.5	219	500	1	1
NA60GRGR.2003.6000	DN200	219	08596683018729	3	6	219	6,000	1	1
NA60GRGR.2504.1000	DN250	273	08596683018330	4	1	273	1,000	1	1
NA60GRGR.2504.3000	DN250	273	08596683018545	4	3	273	3,000	1	1
NA60GRGR.2504.500	DN250	273	08596683018125	4	0.5	273	500	1	1

Code	DN	OD	EAN	T (mm)	L (m)	D	L	Bag	Box
NA60GRGR.2504.6000	DN250	273	08596683018750	4	6	273	6,000	1	1
NA60GRGR.3004.1000	DN300	323.9	08596683018361	4	1	323.9	1,000	1	1
NA60GRGR.3004.3000	DN300	323.9	08596683018576	4	3	323.9	3,000	1	1
NA60GRGR.3004.500	DN300	323.9	08596683018156	4	0.5	323.9	500	1	1
NA60GRGR.3004.6000	DN300	323.9	08596683018781	4	6	323.9	6,000	1	1

Technical data

Material	1.4307 / SS304L (AISI 304L)
Seal type	EPDM elastomer
Grooved system	TGS — rolled groove
Nominal pressure	1.6 MPa (PN 16)
Max. temperature	drinking water 80 °C, other media (e.g. heating) 110 °C
Certification	ITC, CCZ, ISO 9001, ISO 14001 (importer)