


PRESS 316L Elbow (FxRp)

Family: OB12FRP · 8 variants



Product image



Technical drawing

Product description

The TAVINOX PRESS threaded elbow 90° (FxRp) is a 90° elbow with one press end. Taper thread: ISO 7-1. Using the TAVINOX PRESS system, you can install pipework quickly, easily and cleanly. TAVINOX PRESS provides a complete pipework system suitable for every conceivable application.

- ✓ Includes a blue unpressed-joint indicator.
- ✓ Detection of unpressed joints via the Leak Detect system.
- ✓ The QR code on the fitting carries all the technical information.

Dimension table

Code	Dimension	EAN	L1	L2	L3	L4	Bag	Box
OB12FRP.1512	15 mm x 1/2"	08596683007587	20	45	29	45.5	10	100
OB12FRP.1812	18 mm x 1/2"	08596683007617	20	50	29	50.5	10	80
OB12FRP.1834	18 mm x 3/4"	08596683007648	20	50	30	51.5	10	70
OB12FRP.2234 *	22 mm x 3/4"	08596683007679	20.5	57	30	56	10	60
OB12FRP.281 *	28 mm x 1"	08596683007709	22.5	68	33.5	68	5	40
OB12FRP.3554 *	35 mm x 5/4"	08596683007730	26	73.5	36	72	5	25
OB12FRP.4264 *	42 mm x 6/4"	08596683007761	30	85.3	38	81.5	1	20
OB12FRP.542 *	54 mm x 2"	08596683007792	34.5	105	44	101	1	10

* Fire certification VdS / PAVUS

Technical data

Material	Stainless steel AISI 316L (1.4404)
Seal type	EPDM O-ring
Certification	CCZ, ITC, DVGW, EPD, ISO