


GROOVE 304 Elbow

Family: OB62GRGR · 5 variants



The photo shows the AISI 316L version. The supplied version is made of AISI 304 (1.4301) stainless steel and differs in material and marking.

Illustrative photo



Technical drawing

Product description

TAVINOX GROOVE grooved fitting in AISI 304 (1.4301) stainless steel. The clamping coupling with an EPDM elastomer gasket and the TGS rolled groove allows fast installation without welding, with high resistance to vibration and the option to dismantle the joint. Intended for a nominal pressure up to 1.6 MPa; drinking water up to 80 °C, other media (e.g. heating) up to 110 °C.

Dimension table

Code	DN	OD	EAN	D	L	Bag	Box
OB62GRGR.125	DN125	133	08596683013175	133	174	1	1
OB62GRGR.150	DN150	159	08596683013205	159	200	1	1
OB62GRGR.200	DN200	219	08596683013236	219	250	1	1
OB62GRGR.250	DN250	273	08596683013267	273	324	1	1
OB62GRGR.300	DN300	323.9	08596683013298	323.9	367	1	1

Technical data

Material	1.4301 / SS304 (AISI 304)
Seal type	EPDM elastomer
Grooved system	TGS — rolled groove
Nominal pressure	1.6 MPa (PN 16)
Max. temperature	drinking water 80 °C, other media (e.g. heating) 110 °C
Certification	ITC, CCZ, ISO 9001, ISO 14001 (importer)