


PRESS 316L Threaded adaptor (FxF)

Family: PR10FF - 7 variants



Product image



Technical drawing

Product description

The TAVINOX PRESS union coupling (FxF) is a straight coupling with two press ends. Taper thread: ISO 7-1. Using the TAVINOX PRESS system, you can install pipework quickly, easily and cleanly. TAVINOX PRESS provides a complete pipework system suitable for every conceivable application.

- ✓ Includes a blue unpressed-joint indicator.
- ✓ Detection of unpressed joints via the Leak Detect system.
- ✓ The QR code on the fitting carries all the technical information.

Dimension table

Code	Dimension	EAN	L	L1	L2	L3	Bag	Box
PR10FF.15	15 mm	08596683009956	58	20	29.5	59.5	5	80
PR10FF.18	18 mm	08596683009987	61	20	31.5	61.5	5	60
PR10FF.22	22 mm	08596683010013	60	20.5	31.5	63.5	5	50
PR10FF.28	28 mm	08596683010044	66	22.5	35	71	1	40
PR10FF.35	35 mm	08596683010075	72.5	26	37.5	76.5	1	15
PR10FF.42	42 mm	08596683010105	83	30	39	81	1	10
PR10FF.54	54 mm	08596683010136	96	34.5	47.5	93.5	1	5

Technical data

Material	Stainless steel AISI 316L (1.4404)
Seal type	EPDM O-ring
Certification	CCZ, ITC, DVGW, EPD, ISO