


PRESS 316L Threaded adaptor (FxR)

Family: **PR10FR** · 22 variants



Product image



Technical drawing

Product description

The TAVINOX PRESS male adaptor (FxR) is a stainless steel transition fitting with one press end. Taper thread: ISO 7-1. Using the TAVINOX PRESS system, you can install pipework quickly, easily and cleanly. TAVINOX PRESS provides a complete pipework system suitable for every conceivable application.

- ✓ Includes a blue unpressed-joint indicator.
- ✓ Detection of unpressed joints via the Leak Detect system.
- ✓ The QR code on the fitting carries all the technical information.

Dimension table

Code	Dimension	EAN	L	L1	L2	Bag	Box
PR10FR.1512	15 mm x 1/2"	08596683005255	59.5	20	29.5	10	180
PR10FR.1534	15 mm x 3/4"	08596683005286	62.5	20	30.5	10	130
PR10FR.1538	15 mm x 3/8"	08596683005316	53.5	20	29.5	10	180
PR10FR.1812	18 mm x 1/2"	08596683005347	61.5	20	31.5	10	150
PR10FR.1834	18 mm x 3/4"	08596683005378	63.5	20	31.5	10	130
PR10FR.2212 *	22 mm x 1/2"	08596683005408	61.5	20.5	31.5	10	130
PR10FR.2234 *	22 mm x 3/4"	08596683005439	63.5	20.5	31.5	10	120
PR10FR.221 *	22 mm x 1"	08596683005460	69.5	20.5	33.5	10	90
PR10FR.2812 *	28 mm x 1/2"	08596683005491	70	22.5	40	5	100
PR10FR.2834 *	28 mm x 3/4"	08596683005521	61.5	22.5	29.5	5	100
PR10FR.281 *	28 mm x 1"	08596683005552	71	22.5	35	5	70
PR10FR.2854 *	28 mm x 5/4"	08596683005583	78	22.5	39	5	70
PR10FR.351 *	35 mm x 1"	08596683005613	73.5	26	37.5	5	40
PR10FR.3554 *	35 mm x 5/4"	08596683005644	76.5	26	37.5	5	40
PR10FR.3564 *	35 mm x 6/4"	08596683005675	80	26	38	1	30
PR10FR.4254 *	42 mm x 5/4"	08596683005705	78	30	39	1	30
PR10FR.4264 *	42 mm x 6/4"	08596683005736	81	30	39	1	30
PR10FR.5464 *	54 mm x 6/4"	08596683005767	89.5	34.5	47.5	1	20
PR10FR.542 *	54 mm x 2"	08596683005798	93.5	34.5	47.5	1	20
PR10FR.76212 *	76,1 mm x 2 1/2"	08596683005828	127.5	51.5	67.5	1	9
PR10FR.883 *	88,9 mm x 3"	08596683005859	144.5	58	78	1	4

Code	Dimension	EAN	L	L1	L2	Bag	Box
PR10FR.1084 *	108 mm x 4"	08596683005880	170	72	94	1	2

* Fire certification VdS / PAVUS

Technical data

Material	Stainless steel AISI 316L (1.4404)
Seal type	EPDM O-ring
Certification	CCZ, ITC, DVGW, EPD, ISO