



GROOVE 316L Grooved × Press Reducing Adaptor DN150/100


Product code: PR14GRF.150100

DN150/100

EAN: 08596683016923



Product image



Technical drawing

Product description

TAVINOX GROOVE grooved fitting in AISI 316L (1.4404) stainless steel. The clamping coupling with an EPDM elastomer gasket and the TGS rolled groove allows fast installation without welding, with high resistance to vibration and the option to dismantle the joint. Intended for a nominal pressure up to 1.6 MPa; drinking water up to 80 °C, other media (e.g. heating) up to 110 °C.

Technical data

|                    |                                                         |
|--------------------|---------------------------------------------------------|
| Nominal size DN    | DN150/100                                               |
| Size (OD)          | 159,0×108,0 mm                                          |
| D (outside ø)      | 159 mm                                                  |
| d (reduced end)    | 108 mm                                                  |
| L (overall length) | 212 mm                                                  |
| Material           | 1.4404 / SS316L (AISI 316L)                             |
| Seal type          | EPDM elastomer                                          |
| Grooved system     | TGS — rolled groove                                     |
| Nominal pressure   | 1.6 MPa (PN 16)                                         |
| Max. temperature   | drinking water 80 °C, other media (e.g. heating) 110 °C |
| Certification      | ITC, CCZ, ISO 9001, ISO 14001 (importer)                |