



GROOVE 316L Grooved Reducer DN250/200


Product code: PR14GRGR.250200

DN250/200

EAN: 08596683016329



Product image



Technical drawing

Product description

TAVINOX GROOVE grooved fitting in AISI 316L (1.4404) stainless steel. The clamping coupling with an EPDM elastomer gasket and the TGS rolled groove allows fast installation without welding, with high resistance to vibration and the option to dismantle the joint. Intended for a nominal pressure up to 1.6 MPa; drinking water up to 80 °C, other media (e.g. heating) up to 110 °C.

Technical data

|                    |                                                         |
|--------------------|---------------------------------------------------------|
| Nominal size DN    | DN250/200                                               |
| Size (OD)          | 273,0×219,0 mm                                          |
| D (outside Ø)      | 273 mm                                                  |
| d (reduced end)    | 219 mm                                                  |
| L (overall length) | 175 mm                                                  |
| Material           | 1.4404 / SS316L (AISI 316L)                             |
| Seal type          | EPDM elastomer                                          |
| Grooved system     | TGS — rolled groove                                     |
| Nominal pressure   | 1.6 MPa (PN 16)                                         |
| Max. temperature   | drinking water 80 °C, other media (e.g. heating) 110 °C |
| Certification      | ITC, CCZ, ISO 9001, ISO 14001 (importer)                |