


GROOVE 304 Reducer / adaptor

Family: **PR64GRGR** · 10 variants



The photo shows the AISI 316L version. The supplied version is made of AISI 304 (1.4301) stainless steel and differs in material and marking.

Illustrative photo



Technical drawing

Product description

TAVINOX GROOVE grooved fitting in AISI 304 (1.4301) stainless steel. The clamping coupling with an EPDM elastomer gasket and the TGS rolled groove allows fast installation without welding, with high resistance to vibration and the option to dismantle the joint. Intended for a nominal pressure up to 1.6 MPa; drinking water up to 80 °C, other media (e.g. heating) up to 110 °C.

Dimension table

Code	DN	OD	EAN	D	d	L	Bag	Box
PR64GRGR.150125	DN150/125	159,0x133,0	08596683013779	159	133	150	1	1
PR64GRGR.200125	DN200/125	219,0x133,0	08596683013809	219	133	172	1	1
PR64GRGR.200150	DN200/150	219,0x159,0	08596683013830	219	159	163	1	1
PR64GRGR.250125	DN250/125	273,0x133,0	08596683013861	273	133	160	1	1
PR64GRGR.250150	DN250/150	273,0x159,0	08596683013892	273	159	179	1	1
PR64GRGR.250200	DN250/200	273,0x219,0	08596683013922	273	219	175	1	1
PR64GRGR.300125	DN300/125	323,9x133,0	08596683013953	323.9	133	178	1	1
PR64GRGR.300150	DN300/150	323,9x159,0	08596683013984	323.9	159	194	1	1
PR64GRGR.300200	DN300/200	323,9x219,0	08596683014011	323.9	219	172	1	1
PR64GRGR.300250	DN300/250	323,9x273,0	08596683014042	323.9	273	204	1	1

Technical data

Material	1.4301 / SS304 (AISI 304)
Seal type	EPDM elastomer
Grooved system	TGS — rolled groove
Nominal pressure	1.6 MPa (PN 16)
Max. temperature	drinking water 80 °C, other media (e.g. heating) 110 °C
Certification	ITC, CCZ, ISO 9001, ISO 14001 (importer)