


GROOVE 316L Tee

Family: TK14GRGRGR - 10 variants



Product image



Technical drawing

Product description

TAVINOX GROOVE grooved fitting in AISI 316L (1.4404) stainless steel. The clamping coupling with an EPDM elastomer gasket and the TGS rolled groove allows fast installation without welding, with high resistance to vibration and the option to dismantle the joint. Intended for a nominal pressure up to 1.6 MPa; drinking water up to 80 °C, other media (e.g. heating) up to 110 °C.

Dimension table

Code	DN	OD	EAN	D	d	L	H	Bag	Box
TK14GRGRGR.150125	DN150/125	159,0×133,0	08596683016473	159	133	143	168	1	1
TK14GRGRGR.200125	DN200/125	219,0×133,0	08596683016503	219	133	178	200	1	1
TK14GRGRGR.200150	DN200/150	219,0×159,0	08596683016534	219	159	178	197	1	1
TK14GRGRGR.250125	DN250/125	273,0×133,0	08596683016565	273	133	170	217	1	1
TK14GRGRGR.250150	DN250/150	273,0×159,0	08596683016596	273	159	180	217	1	1
TK14GRGRGR.250200	DN250/200	273,0×219,0	08596683016626	273	219	216	217	1	1
TK14GRGRGR.300125	DN300/125	323,9×133,0	08596683016657	323.9	133	170	243	1	1
TK14GRGRGR.300150	DN300/150	323,9×159,0	08596683016688	323.9	159	180	243	1	1
TK14GRGRGR.300200	DN300/200	323,9×219,0	08596683016718	323.9	219	205	243	1	1
TK14GRGRGR.300250	DN300/250	323,9×273,0	08596683016749	323.9	273	254	243	1	1

Technical data

Material	1.4404 / SS316L (AISI 316L)
Seal type	EPDM elastomer
Grooved system	TGS — rolled groove
Nominal pressure	1.6 MPa (PN 16)
Max. temperature	drinking water 80 °C, other media (e.g. heating) 110 °C
Certification	ITC, CCZ, ISO 9001, ISO 14001 (importer)