



GROOVE 304 Grooved Reducing Tee DN200/150

Product code: TK64GRGRGR.200150


DN200/150

EAN: 08596683014134



The photo shows the AISI 316L version. The supplied version is made of AISI 304 (1.4301) stainless steel and differs in material and marking.

Illustrative photo



Technical drawing

Product description

TAVINOX GROOVE grooved fitting in AISI 304 (1.4301) stainless steel. The clamping coupling with an EPDM elastomer gasket and the TGS rolled groove allows fast installation without welding, with high resistance to vibration and the option to dismantle the joint. Intended for a nominal pressure up to 1.6 MPa; drinking water up to 80 °C, other media (e.g. heating) up to 110 °C.

Technical data

|                    |                                                         |
|--------------------|---------------------------------------------------------|
| Nominal size DN    | DN200/150                                               |
| Size (OD)          | 219,0×159,0 mm                                          |
| D (outside ø)      | 219 mm                                                  |
| d (reduced end)    | 159 mm                                                  |
| L (overall length) | 178 mm                                                  |
| H (height)         | 197 mm                                                  |
| Material           | 1.4301 / SS304 (AISI 304)                               |
| Seal type          | EPDM elastomer                                          |
| Grooved system     | TGS — rolled groove                                     |
| Nominal pressure   | 1.6 MPa (PN 16)                                         |
| Max. temperature   | drinking water 80 °C, other media (e.g. heating) 110 °C |
| Certification      | ITC, CCZ, ISO 9001, ISO 14001 (importer)                |