



GROOVE 304 Grooved Reducing Tee DN250/125

Product code: TK64GRGRGR.250125


DN250/125

EAN: 08596683014165



The photo shows the AISI 316L version. The supplied version is made of AISI 304 (1.4301) stainless steel and differs in material and marking.

Illustrative photo



Technical drawing

Product description

TAVINOX GROOVE grooved fitting in AISI 304 (1.4301) stainless steel. The clamping coupling with an EPDM elastomer gasket and the TGS rolled groove allows fast installation without welding, with high resistance to vibration and the option to dismantle the joint. Intended for a nominal pressure up to 1.6 MPa; drinking water up to 80 °C, other media (e.g. heating) up to 110 °C.

Technical data

Nominal size DN	DN250/125
Size (OD)	273,0×133,0 mm
D (outside ø)	273 mm
d (reduced end)	133 mm
L (overall length)	170 mm
H (height)	217 mm
Material	1.4301 / SS304 (AISI 304)
Seal type	EPDM elastomer
Grooved system	TGS — rolled groove
Nominal pressure	1.6 MPa (PN 16)
Max. temperature	drinking water 80 °C, other media (e.g. heating) 110 °C
Certification	ITC, CCZ, ISO 9001, ISO 14001 (importer)