



GROOVE 304 Grooved Reducing Tee DN300/200

Product code: TK64GRGRGR.300200


DN300/200

EAN: 08596683014318



The photo shows the AISI 316L version. The supplied version is made of AISI 304 (1.4301) stainless steel and differs in material and marking.

Illustrative photo



Technical drawing

Product description

TAVINOX GROOVE grooved fitting in AISI 304 (1.4301) stainless steel. The clamping coupling with an EPDM elastomer gasket and the TGS rolled groove allows fast installation without welding, with high resistance to vibration and the option to dismantle the joint. Intended for a nominal pressure up to 1.6 MPa; drinking water up to 80 °C, other media (e.g. heating) up to 110 °C.

Technical data

Nominal size DN	DN300/200
Size (OD)	323,9×219,0 mm
D (outside ø)	323.9 mm
d (reduced end)	219 mm
L (overall length)	205 mm
H (height)	243 mm
Material	1.4301 / SS304 (AISI 304)
Seal type	EPDM elastomer
Grooved system	TGS — rolled groove
Nominal pressure	1.6 MPa (PN 16)
Max. temperature	drinking water 80 °C, other media (e.g. heating) 110 °C
Certification	ITC, CCZ, ISO 9001, ISO 14001 (importer)