GROOVE 304 Tee

Family: **TK64GRGRGR** · 10 variants

The photo shows the AISI 316L version. The supplied version is made of AISI 304 (1.4301) stainless steel and differs in material and marking.

Illustrative photo



Technical drawing

Product description

TAVINOX GROOVE grooved fitting in AISI 304 (1.4301) stainless steel. The clamping coupling with an EPDM elastomer gasket and the TGS rolled groove allows fast installation without welding, with high resistance to vibration and the option to dismantle the joint. Intended for a nominal pressure up to 1.6 MPa; drinking water up to 80 °C, other media (e.g. heating) up to 110 °C.

Dimension table

Code	DN	OD	EAN	D	d	L	H	Bag	Box
TK64GRGRGR.150125	DN150/125	159,0×133,0	08596683014073	159	133	143	168	1	1
TK64GRGRGR.200125	DN200/125	219,0×133,0	08596683014103	219	133	178	200	1	1
TK64GRGRGR.200150	DN200/150	219,0×159,0	08596683014134	219	159	178	197	1	1
TK64GRGRGR.250125	DN250/125	273,0×133,0	08596683014165	273	133	170	217	1	1
TK64GRGRGR.250150	DN250/150	273,0×159,0	08596683014196	273	159	180	217	1	1
TK64GRGRGR.250200	DN250/200	273,0×219,0	08596683014226	273	219	216	217	1	1
TK64GRGRGR.300125	DN300/125	323,9×133,0	08596683014257	323.9	133	170	243	1	1
TK64GRGRGR.300150	DN300/150	323,9×159,0	08596683014288	323.9	159	180	243	1	1
TK64GRGRGR.300200	DN300/200	323,9×219,0	08596683014318	323.9	219	205	243	1	1
TK64GRGRGR.300250	DN300/250	323,9×273,0	08596683014349	323.9	273	254	243	1	1

Technical data

Material	1.4301 / SS304 (AISI 304)
Seal type	EPDM elastomer
Grooved system	TGS — rolled groove
Nominal pressure	1.6 MPa (PN 16)
Max. temperature	drinking water 80 °C, other media (e.g. heating) 110 °C
Certification	ITC, CCZ, ISO 9001, ISO 14001 (importer)

© 1999–2026 tavinox.com / CZECH STYLE, spol. s r.o.