

GROOVE 304 Pipes

Family: TR60GRGR · 14 variants



Product image

Drawing not available

Technical drawing

Product description

TAVINOX GROOVE stainless steel pipe in AISI 304 (1.4301). The TGS rolled groove provides a fast, secure and demountable joint without welding. Intended for drinking water pipework, building services, industrial pipework and fire protection at a nominal pressure up to 1.6 MPa and an operating temperature up to 110 °C.

Dimension table

| Code                | DN    | OD    | EAN            | T (mm) | L (m) | Bag | Box |
|---------------------|-------|-------|----------------|--------|-------|-----|-----|
| TR60GRGR.12525.3000 | DN125 | 133   | 08596683019658 | 2.5    | 3     | 1   | 1   |
| TR60GRGR.12525.6000 | DN125 | 133   | 08596683019863 | 2.5    | 6     | 1   | 1   |
| TR60GRGR.1253.3000  | DN125 | 133   | 08596683019689 | 3      | 3     | 1   | 1   |
| TR60GRGR.1253.6000  | DN125 | 133   | 08596683019894 | 3      | 6     | 1   | 1   |
| TR60GRGR.15025.3000 | DN150 | 159   | 08596683019719 | 2.5    | 3     | 1   | 1   |
| TR60GRGR.15025.6000 | DN150 | 159   | 08596683019924 | 2.5    | 6     | 1   | 1   |
| TR60GRGR.1503.3000  | DN150 | 159   | 08596683019740 | 3      | 3     | 1   | 1   |
| TR60GRGR.1503.6000  | DN150 | 159   | 08596683019955 | 3      | 6     | 1   | 1   |
| TR60GRGR.2003.3000  | DN200 | 219   | 08596683019771 | 3      | 3     | 1   | 1   |
| TR60GRGR.2003.6000  | DN200 | 219   | 08596683019986 | 3      | 6     | 1   | 1   |
| TR60GRGR.2504.3000  | DN250 | 273   | 08596683019801 | 4      | 3     | 1   | 1   |
| TR60GRGR.2504.6000  | DN250 | 273   | 08596683020012 | 4      | 6     | 1   | 1   |
| TR60GRGR.3004.3000  | DN300 | 323.9 | 08596683019832 | 4      | 3     | 1   | 1   |
| TR60GRGR.3004.6000  | DN300 | 323.9 | 08596683020043 | 4      | 6     | 1   | 1   |

Technical data

|                            |                                                      |
|----------------------------|------------------------------------------------------|
| Material                   | 1.4301 / SS304 (AISI 304)                            |
| Seal type                  | EPDM elastomer                                       |
| Grooved system             | TGS — rolled groove                                  |
| Nominal pressure           | 1.6 MPa (PN 16)                                      |
| Max. operating temperature | 110 °C                                               |
| Certification              | DVGW, ITC, ISO 9001, ISO 14001, CCZ, EPD coming soon |